



Glazing 1	PLANICLEAR 4 mm PLANITHERM XN
Cavity 1	Argon 90% 16 mm
Glazing 2	PLANICLEAR 4 mm

Last name: Rolloplast Agiannidis

Country: Greece

Notes: Example for www.rolloplast.gr

LUMINOUS FACTORS EN410 (2011-04)

Light Transmittance (TL)	82 %
Outdoor Reflectance (RLe)	12 %
Indoor Reflectance (RLi)	11 %

THERMAL TRANSMISSION EN673-2011

Ug	1.1 W/(m ² .K)
Angle relative to the vertical	0 °

MANUFACTURING SIZES

Nominal Thickness	24.00 mm
Weight	20.0 kg/m ²

ACOUSTICS EN 12758

Acoustic values according to EN 12758 and from notified body

Rw (C;Ctr)	31 (-1; -4) dB
STC (ASTM E413)	N/A
OITC (ASTM E1332)	N/A

SAFETY CLASS EN 12600

Pendulum Body Resistance	NPD
--------------------------	-----

ENERGY FACTORS EN410 (2011-04)

Transmittance (TE)	60 %
Outdoor Reflectance (Ree)	27 %
Indoor Reflectance (Rei)	27 %
Absorptance A1 (AE1)	11 %
Absorptance A2 (AE2)	3 %

SOLAR FACTORS EN410 (2011-04)

Solar Factor (g)	0.62
Shading Coefficient (SC)	0.72

COLOR RENDERING

Transmission (Ra)	98
Reflection (Ra)	95

ANTI-BURGLARY EN 356

Burglar Resistance	NPD
--------------------	-----

