



Glazing 1

PLANICLEAR 10 mm

Last name: Rolloplast Agiannidis

Country: Greece

Notes: Example for www.rolloplast.gr

 **LUMINOUS FACTORS** EN410 (2011-04)

Light Transmittance (TL)	89 %
Outdoor Reflectance (RLe)	8 %
Indoor Reflectance (RLi)	8 %

 **THERMAL TRANSMISSION** EN673-2011

Ug	5.6 W/(m ² .K)
Angle relative to the vertical	0 °

 **MANUFACTURING SIZES**

Nominal Thickness	10.00 mm
Weight	25.0 kg/m ²

 **ACOUSTICS** EN 12758

Acoustic values according to EN 12758 and from notified body

Rw (C;Ctr)	35 (-1; -2) dB
STC (ASTM E413)	N/A
OITC (ASTM E1332)	N/A

 **SAFETY CLASS** EN 12600

Pendulum Body Resistance	NPD
--------------------------	-----

 **ENERGY FACTORS** EN410 (2011-04)

Transmittance (TE)	81 %
Outdoor Reflectance (Ree)	7 %
Indoor Reflectance (Rei)	7 %
Absorptance A1 (AE1)	12 %

 **SOLAR FACTORS** EN410 (2011-04)

Solar Factor (g)	0.84
Shading Coefficient (SC)	0.96

 **COLOR RENDERING**

Transmission (Ra)	98
Reflection (Ra)	98

 **ANTI-BURGLARY** EN 356

Burglar Resistance	NPD
--------------------	-----

