



Glazing 1

PLANICLEAR 3 mm
PVB SILENCE 0.38 mm
PLANICLEAR 3 mm

Last name: Rolloplast Agiannidis

Country: Greece

Notes: Example for www.rolloplast.gr

LUMINOUS FACTORS EN410 (2011-04)

Light Transmittance (TL)	90 %
Outdoor Reflectance (RLe)	8 %
Indoor Reflectance (RLi)	8 %

THERMAL TRANSMISSION EN673-2011

Ug	5.6 W/(m².K)
Angle relative to the vertical	0 °

MANUFACTURING SIZES

Nominal Thickness	6.38 mm
Weight	15.4 kg/m²

ACOUSTICS EN 12758

Acoustic values according to EN 12758 and from notified body

Rw (C;Ctr)	35 (0; -3) dB
STC (ASTM E413)	N/A
OITC (ASTM E1332)	N/A

SAFETY CLASS EN 12600

Pendulum Body Resistance	2B2
--------------------------	-----

ENERGY FACTORS EN410 (2011-04)

Transmittance (TE)	80 %
Outdoor Reflectance (Ree)	7 %
Indoor Reflectance (Rei)	7 %
Absorptance A1 (AE1)	13 %

SOLAR FACTORS EN410 (2011-04)

Solar Factor (g)	0.83
Shading Coefficient (SC)	0.95

COLOR RENDERING

Transmission (Ra)	99
Reflection (Ra)	98

ANTI-BURGLARY EN 356

Burglar Resistance	NPD
--------------------	-----

