



Glazing 1	PLANICLEAR 4 mm
Cavity 1	AIR 12 mm
Glazing 2	PLANICLEAR 6 mm

Last name: Rolloplast Agiannidis

Country: Greece

Notes: Example for [www.rolloplast.gr](http://www.rolloplast.gr)

**LUMINOUS FACTORS** EN410 (2011-04)

Light Transmittance (TL)	82 %
Outdoor Reflectance (RLe)	15 %
Indoor Reflectance (RLi)	15 %

**THERMAL TRANSMISSION** EN673-2011

Ug	2.8 W/(m².K)
Angle relative to the vertical	0 °

**MANUFACTURING SIZES**

Nominal Thickness	22.00 mm
Weight	25.0 kg/m²

**ACOUSTICS** EN 12758

*Acoustic simulated values*

Rw (C;Ctr)	34 (-1; -4) dB
STC (ASTM E413)	34
OITC (ASTM E1332)	28

**SAFETY CLASS** EN 12600

Pendulum Body Resistance	NPD
--------------------------	-----

**ENERGY FACTORS** EN410 (2011-04)

Transmittance (TE)	75 %
Outdoor Reflectance (Ree)	14 %
Indoor Reflectance (Rei)	13 %
Absorptance A1 (AE1)	5 %
Absorptance A2 (AE2)	6 %

**SOLAR FACTORS** EN410 (2011-04)

Solar Factor (g)	0.79
Shading Coefficient (SC)	0.91

**COLOR RENDERING**

Transmission (Ra)	98
Reflection (Ra)	98

**ANTI-BURGLARY** EN 356

Burglar Resistance	NPD
--------------------	-----

