



Glazing 1	PLANICLEAR 4 mm
Cavity 1	AIR 15 mm
Glazing 2	PLANICLEAR 4 mm

Last name: Rolloplast Agiannidis

Country: Greece

Notes: Example for [www.rolloplast.gr](http://www.rolloplast.gr)

**LUMINOUS FACTORS** EN410 (2011-04)

Light Transmittance (TL)	83 %
Outdoor Reflectance (RLe)	15 %
Indoor Reflectance (RLi)	15 %

**THERMAL TRANSMISSION** EN673-2011

Ug	2.7 W/(m².K)
Angle relative to the vertical	0 °

**MANUFACTURING SIZES**

Nominal Thickness	23.00 mm
Weight	20.0 kg/m²

**ACOUSTICS** EN 12758

*Acoustic simulated values*

Rw (C;Ctr)	32 (-1; -4) dB
STC (ASTM E413)	32
OITC (ASTM E1332)	26

**SAFETY CLASS** EN 12600

Pendulum Body Resistance	NPD
--------------------------	-----

**ENERGY FACTORS** EN410 (2011-04)

Transmittance (TE)	77 %
Outdoor Reflectance (Ree)	14 %
Indoor Reflectance (Rei)	14 %
Absorptance A1 (AE1)	5 %
Absorptance A2 (AE2)	4 %

**SOLAR FACTORS** EN410 (2011-04)

Solar Factor (g)	0.80
Shading Coefficient (SC)	0.92

**COLOR RENDERING**

Transmission (Ra)	99
Reflection (Ra)	98

**ANTI-BURGLARY** EN 356

Burglar Resistance	NPD
--------------------	-----

