



Glazing 1 PLANICLEAR 4 mm

Last name: Rolloplast Agiannidis
Country: Greece

Notes: Example for www.rolloplast.gr

	LUMINOUS FACTORS	EN410 (2011-04)
	Light Transmittance (TL)	91 %
	Outdoor Reflectance (RLe)	8 %
	Indoor Reflectance (RLi)	8 %

	ENERGY FACTORS	EN410 (2011-04)
	Transmittance (TE)	87 %
	Outdoor Reflectance (Ree)	8 %
	Indoor Reflectance (Rei)	8 %
	Absorptance A1 (AE1)	5 %

	THERMAL TRANSMISSION	EN673-2011
	Ug	5.8 W/(m².K)
	Angle relative to the vertical	0 °

	SOLAR FACTORS	EN410 (2011-04)
	Solar Factor (g)	0.88
	Shading Coefficient (SC)	1.01

	MANUFACTURING SIZES	
	Nominal Thickness	4.00 mm
	Weight	10.0 kg/m²

	COLOR RENDERING	
	Transmission (Ra)	99
	Reflection (Ra)	99

	ACOUSTICS	EN 12758
	<i>Acoustic values according to EN 12758 and from notified body</i>	
	Rw (C;Ctr)	30 (-2; -2) dB
	STC (ASTM E413)	N/A
	OITC (ASTM E1332)	N/A

	ANTI-BURGLARY	EN 356
	Burglar Resistance	NPD

	SAFETY CLASS	EN 12600
	Pendulum Body Resistance	NPD

