



Glazing 1 PLANICLEAR 8 mm

Last name: Rolloplast Agiannidis

Country: Greece

Notes: Example for www.rolloplast.gr

 **LUMINOUS FACTORS** EN410 (2011-04)

Light Transmittance (TL)	89 %
Outdoor Reflectance (RLe)	8 %
Indoor Reflectance (RLi)	8 %

 **THERMAL TRANSMISSION** EN673-2011

Ug	5.6 W/(m ² .K)
Angle relative to the vertical	0 °

 **MANUFACTURING SIZES**

Nominal Thickness	8.00 mm
Weight	20.0 kg/m ²

 **ACOUSTICS** EN 12758

Acoustic values according to EN 12758 and from notified body

Rw (C;Ctr)	33 (-1; -2) dB
STC (ASTM E413)	N/A
OITC (ASTM E1332)	N/A

 **SAFETY CLASS** EN 12600

Pendulum Body Resistance	NPD
--------------------------	-----

 **ENERGY FACTORS** EN410 (2011-04)

Transmittance (TE)	83 %
Outdoor Reflectance (Ree)	8 %
Indoor Reflectance (Rei)	8 %
Absorptance A1 (AE1)	10 %

 **SOLAR FACTORS** EN410 (2011-04)

Solar Factor (g)	0.85
Shading Coefficient (SC)	0.98

 **COLOR RENDERING**

Transmission (Ra)	99
Reflection (Ra)	98

 **ANTI-BURGLARY** EN 356

Burglar Resistance	NPD
--------------------	-----

